

PETRO FACTS



SONIC® MP GEAR OIL SL SYNTHETIC GEAR OIL



**SONIC®
MP GEAR OIL SL**
is available in:

- 20 litre pail

DESCRIPTION

SONIC® MP GEAR OIL SL is a synthetic-based, heavy-duty gear lubricant that is blended for year-round applications, including sub-zero operating conditions. It is approved for extended drain application and extended warranty (750,000 mile Eaton Roadranger) requirements.

FEATURES & BENEFITS

- **GEAR PROTECTION**
Contains extreme pressure additives to protect gears under severe operating conditions.
- **CORROSION PROTECTION**
Offers superior protection against rust and corrosion.
- **SEAL COMPATIBILITY**
Compatible with most seal components used today.
- **LIMITED SLIP**
75W90 and 80W140 are compatible with limited slip applications.
- **OXIDATION STABILITY**
Offers superior oxidation stability even under extreme heat conditions.
- **ECONOMY**
Improves vehicle economy due to superior low temperature fluidity and oil film strength.
- **WARRANTY APPROVALS**
 - Eaton PS-037
 - Rockwell O-76-E and O-76B
 - Roadranger extended warranty

NOTE: Not recommended for use with silicone seals and gaskets.

APPLICATION

- **SONIC MP GEAR OIL SL** is recommended for use in any application requiring a heavy-duty, extreme-pressure, GL5 gear lubricant. It is recommended for complete refills only.

TYPICAL PROPERTIES

● SAE GRADE	75W90	50	80W140
Viscosity @40°C, cst	126	135	271
Viscosity @100°C, cst	17.3	18.2	30.5
Viscosity Index	151	151	152
Pour Point, 0°C	<-51°C	<-40°C	<-32°C

RECYCLABLE
www.mtm.ca



Printed in Canada
with vegetable based ink

